

# **THE NEW VIEW-LITE 0515LD AC AND DC OPERATING INDUSTRIAL X-RAY LED FILM VIEWER WITH BUILT-IN FILM DENSITOMETER**



## **FEATURES :**

- CAN WORKING WITH AC POWER OR DC RECHARGEABLE BATTERY PACK
- HIGH INTENSITY TO VIEW 4.5D
- PORTABLE WITH ADJUSTABLE HANDLE AND FOOT SWITCH
- BUILT-IN DENSITOMETER

## **SPECIFICATION :**

- LIGHT INTENSITY  $\geq 130000\text{cd/m}^2$
- WINDOW SIZE ( LXW ) : 150mm x 50mm
- CASE MATERIAL : ALUMINUM + SIDE ABS
- LIGHT UNIFORM : 90%
- HEAT ON WINDOW( ROOM TEMPERATURE :25°C ) : 40°C
- DIMER CONTROL : 30-100%
- LIGHT SOURCE : PURE LED
- WEIGHT : 2.2kgw
- POWER REQUIREMENT : 100-240 VAC & DC-18650 BATTERY PACK
- OUTSIDE DIMENSION : 495mm x 225mm x 65mm
- BATTERY PACK : 18650 RECHARGEABLE LITHIUM-ION, 16.8 VDC
- BATTERY OPERATING TIME : 1.5hr WITH MAX. LIGHT INTENSITY
- BATTERY CHARGE TIME : 3.5 HOURS
- RGER : INPUT : 100-240VAC50/60Hz OUTPUT : DC 16.8V - 5A
- DENSITY RANGE : 0-4.0D
- SENSOR : PHOTO IC WITH 1 M LONG CABLE
- SENSOR APERTURE : 2mm and 3 mm
- RESOLUTION : 0.01D
- ACCURACY : +/- 0.03D
- REPEATABILITY : +/- 0.02D

