

# PORTABLE HIGH INTENSITY 35DUV LAMP

HIGH QUALITY RELIABLE MODULE DESIGN FOR NDT APPLICATION  
MEET ASME CODE REQUIREMENT  
CE QUALIFIED APPROVED



MPXL 35DUV



MPXM 35DUV



MPXM-BL 35DUV



AIO-35DUV



FL3 DUV

SPECIFICATION	MPXL 35DUV	MPXM 35DUV	MPXM-BL 35DUV	AIO-35DUV	FL3 DUV
UV BULB	35W DUV	35W DUV	35W DUV	35W DUV	24W DUV
UV WAVE LENGTH	365 nm	365 nm	365 nm	365 nm	365 nm
UV INTENSITY (18")	>25000uw/cm <sup>2</sup>	>25000uw/cm <sup>2</sup>	>25000uw/cm <sup>2</sup>	>25000uw/cm <sup>2</sup>	>14000uw/cm <sup>2</sup>
WARM UP	INSTANT ON/OFF	INSTANT ON/OFF	INSTANT ON/OFF	INSTANT ON/OFF	INSTANT ON/OFF
FAN COOL	YES	YES	YES	—	—
DUTY CYCLE	100%	100%	100%	100%	100%
UV FILTER GLASS DIA	144mm	144mm	144mm	144mm	76mm
UV FILTER GLASS	YES	YES	YES	YES	YES
POWER SUPPLY	AC	AC	DC	DC	DC
BATTERY	—	—	16.8v	16.8v	12v
BATTERY USE HOURS	—	—	4hr	4hr	>3hr
BATTERY CHARGE TIME	—	—	3hr	3hr	3hr
LAMP HEAD DIMENSION ( WITH HANDLE)	—	180X180X250mm	180X180X250mm	—	—
BALLAST DIMENSION ( WITH HANDLE)	230X180X270mm	230X180X180mm	230X180X180mm	230X180X180mm	—
BATTERY DIMENSION	—	—	135X37X72mm 	74x74x28mm 	420x24mm 
LAMP HEAD WEIGHT	—	1.2kg	1.2kg	—	—
BALLAST PACK WEIGHT	1.92kg	2.98kg	3.45kg	2.48kg	1.1kg
BATTERY PACK WEIGHT	—	—	740g	720g	570g
PROTECT CARRY CASE	OPTIOANL	OPTIOANL	OPTIOANL	OPTIOANL	OPTIOANL



## KEIYU NDT SUPPLY CO.

1F., No.409, Sec. 6, Zhongxiao E. Rd., Nangang Dist., Taipei City 115, Taiwan (R.O.C.).  
TEL: 02-26534530 FAX: 02-26547597  
E-Mail : sale@keiyu-ndt.com.tw

Web site: [www.keiyu-ndt.com.tw](http://www.keiyu-ndt.com.tw)

Skype: keiyu-ndt