

HIGH INTENSITY LED X-RAY FILM VIEWER

HIGH QUALITY RELIABLE MODULE DESIGN

MEET EN 25580 1992 & ASTM E1390-90, ISO 558D 1995
CE QUALIFIED APPROVED

0515L



0515BL



SPECIFICATION	0515L	0515BL
LIGHT INTENSITY $\geq$	130000 cd/m ²	130000 cd/m ²
WINDOW SIZE(LXW)	150mm x 50mm	150mm x 50mm
CASE MATERIAL	Aluminum	Aluminum + Abs
LIGHT UNIFORM	90%	90%
HEAT ON WINDOW (ROOM TEMPERATURE:25°C)	40°C	40°C
DIMER CONTROL	30-100%	30-100%
WEIGHT	2.2Kgw	3.5Kgw
ADJUSTABLE HANDLE	Yes	No
LIGHT SOURCE	Pure Led	Pure Led
POWER REQUIREMENT	100-240 VAC & DC-18650	DC-18650
FOOT SWITCH	Yes	No
OUTSIDE DIMENSION	495mm x 225mm x 65mm	408mm x 162mm x 95mm
BATTERY	16.8V(5 A/h)	16.8V(5 A/h)
BATTERY USE HOURS	3hr	3hr
BATTERY CHARGE TIME	6hr	6hr
CHARGER	Input:100-240VAC50/60Hz Output:DC 16.8V - 5A	Input:100-240VAC50/60Hz Output:DC 16.8V - 5A



KEIYU NDT SUPPLY CO.

1F., No.409, Sec. 6, Zhongxiao E. Rd., Nangang Dist., Taipei City 115, Taiwan (R.O.C.)

TEL: 02-26534530 FAX: 02-26547597

E-Mail: sale@keiyu-ndt.com.tw

Web site: www.keiyu-ndt.com.tw

Skype:keiyu-ndt