

HIGH INTENSITY LED X-RAY FILM VIEWER

HIGH QUALITY RELIABLE MODULE DESIGN

MEET EN 25580 1992 & ASTM E1390-90, ISO 558D 1995
CE QUALIFIED APPROVED

8028L



0417L



4010L



4517L



SPECIFICATION	8028L	0417L	4010L	4517L
LIGHT INTENSITY $\geq$	113000 cd/m ²	105000 cd/m ²	110000-115000 cd/m ²	23000-115000 cd/m ²
WINDOW SIZE(LXW)	220mm x 62mm	300mm x 75mm	400mm x 100mm	442mm x 117mm
CASE MATERIAL	Aluminum	Aluminum		Aluminum
LIGHT UNIFORM	90%	90%	85%	90%
HEAT ON WINDOW (ROOM TEMPERATURE:25)	40°C	38°C	45°C	40°C
DIMER CONTROL	25-100%	25-100%	10-100%	30-100%
WEIGHT	3Kgw	3.7Kgw	5.85Kgw	8Kgw
ADJUSTABLE HANDLE	YES	YES	NO	YES
LIGHT SOURCE	PURE LED	PURE LED	PURE LED WITH LENS	PURE LED
POWER REQUIREMENT	100-240 VAC	110 VAC OR 240 VAC	100-240 VAC	100-240 VAC
FOOT SWITCH	YES	YES	YES	YES
OUTSIDE DIMENSION	440mmx170mmx80mm	570mmx170mmx80mm	620mmx165mmx130mm	736mmx260mmx105mm



KEIYU NDT SUPPLY CO.

1F., No.409, Sec. 6, Zhongxiao E. Rd., Nangang Dist., Taipei City 115, Taiwan (R.O.C.).

TEL: 02-26534530 FAX: 02-26547597

E-Mail : sale@keiyu-ndt.com.tw

Web site: www.keiyu-ndt.com.tw

Skype:keiyu-ndt