

HIGH INTENSITY INDUSTRIAL X-RAY FILM VIEWER

HIGH QUALITY RELIABLE MODULE DESIGN

CE QUALIFIED APPROVED

0414G



0417



0417-55



1417



SPECIFICATION	0414G	0417	0417-55	1417
LIGHT INTENSITY $\geq$ cd/m ²	40000 cd/m ²	40000 cd/m ²	40000 cd/m ²	55000 cd/m ²
LIGHT INTENSITY $\geq$ Lux	103000Lux	103000Lux	121000Lux	155000Lux
WINDOW SIZE(LXW)	350mm x 86mm	350mm x 86mm	435mm x 113mm	356mm x 432mm
CASE MATERIAL	Aluminum	Aluminum	Aluminum	Aluminum
HEAT ON WINDOW (ROOM TEMPERATURE:25)	38°C	38°C	38°C	38°C
DIMER CONTROL	20-100%	20-100%	20-100%	20-100%
WEIGHT	2.85Kgw	2.5Kgw	3.3Kgw	7.5Kgw
ADJUSTABLE HANDLE	YES	YES	YES	YES
LIGHT SOURCE	PL36W GREEN BULB	PL36W GREEN BULB	PL55W GREEN BULB	PL36W GREEN BULB
POWER REQUIREMENT	110 VAC OR 220 VAC	110 VAC OR 220 VAC	110 VAC OR 220 VAC	110 VAC OR 220 VAC
FOOT SWITCH	YES	YES	YES	YES
OUTSIDE DIMENSION	570mmx170mmx80mm	490mmx170mmx55mm	715mmx170mmx55mm	572mmx542mmx85mm

- 565nm wave length green light, very good for humaneyes
- PL36W/PL55W Green Bulb can instead by PL36W white lamp but light intensity will change



KEIYU NDT SUPPLY CO.

1F., No.409, Sec. 6, Zhongxiao E. Rd., Nangang Dist., Taipei City 115, Taiwan (R.O.C.).

TEL: 02-26534530 FAX: 02-26547597

E-Mail : sale@keiyu-ndt.com.tw

Web site: www.keiyu-ndt.com.tw

Skype:keiyu-ndt